

Washington Group on Disability Statistics

2020年5月

分析指南: 使用华盛顿小组简易功能问题集(WG-SS)SPSS语法创建 残疾标识符

导言

最好将残疾理解为一个连续体。在功能困难方面,可以通过一系列描述符对"困难"进行操作性定义,从完全没有困难,到有点困难和非常困难,再到完全无法执行动作。这些描述符中的每一个都表示确定最终残疾标识符时的分界点或阈值;例如,用来定义那些有残疾和没有残疾的人。这些功能困难程度也体现在华盛顿小组简易功能问题集(WG-SS)的答案类别中。

残疾发生率不是单一的统计数据,但可以根据数据收集和报告的目的,在各种阈值下进行计算。例如,如果目的是提供公共空间的平等使用权,那么某个残疾标识符的纳入程度可能是"有点困难",因为那些即使是有轻微功能障碍的人也可能会受益于为消除障碍和方便使用而做出的调整。例如,安装自动扶梯取代楼梯,是一种通用的设计元素,行动困难程度不一的人均能从中受益。或者,如果目的是提供补贴或津贴,那么某个残疾标识符的纳入程度可能是"完全无法做到",因为只有那些功能受限更严重的人才符合更严格的资格标准。

本文档中描述的SPSS语法规定了四个阈值下四个残疾标识符的计算方法。使用这四个不同阈值的残疾人群产生以下四个残疾标识符:

《华盛顿小组实施文件》涵盖 了华盛顿残疾统计小组(WG)开 发的、用来在人口普查和调查 中收集国际可比的残疾数据的 多款工具。实施文件介绍了集 施简易问题集、详细问题集、 简易问题集-增强版、华盛顿小组/ 国基会儿童功能模块(2-4岁和5-17岁)、华盛顿小组/国查残 劳工组织(ILO)劳动力调查残 疾模块,以及其他华盛顿小组 下具的最佳实践。主题包括翻 译、问题规范、分析指南、 于分析的编程代码、分类工具的使用等等。

如需查找其他《华盛顿小组 实施文件》和更多信息,请 访问华盛顿小组网站: http://www.washingtongroupdisability.com/。

- **残疾1**: 纳入程度为至少一个领域/问题编码为"有点困难"或"非常困难"或 "完全无法做到"。
- **残疾2**: 纳入程度为至少两个领域/问题编码为"有点困难"或任何一个领域/问题编码为"非常困难"或"完全无法做到"。

• 残疾3: 纳入程度为任何一个领域/问题编码为"非常困难"或"完全无法做到"。

注: 残疾3是华盛顿小组建议的分界点。

• 残疾4: 纳入程度为任何一个领域编码为"完全无法做到"(4)。

注: SPSS语法基于下表所示的*变量标签和数值标签*。确保您使用的是相同的*变量标签和数值标签*,或者修改SPSS语法以反映在数据库中使用的*标签*。

WG-SS作为美国国民健康访谈调查(NHIS)的一部分实施。用于编制这些指南的数据来自2013年的NHIS。

NHIS用户注意: NHIS数据文件和文档中的变量名称可能与本文档中使用的变量名称不同;例如,在本文档中称为SC-SS的自理领域变量在NHIS数据文件和文档中称为UB SS。

华盛顿小组简易问题集中的问题/领域	变量标签
1.即使戴着眼镜,您是否也难以看清楚?	VIS_SS
2.即使使用助听器,您是否也难以听清楚?	HEAR_SS
3.您是否难以正常行走或上下阶梯?	MOB_SS
4.您是否难以记住东西或集中注意力?	COG_SS
5.您是否难以自理生活,例如清洗全身或穿衣?	SC_SS
6.您是否难以使用日常语言和他人沟通,如理解他人或被他人理解?	COM_SS

每个WG-SS问题使用的数值标签为:

- 1. 没有困难
- 2. 是,有点困难
- 3. 是, 非常困难
- 4. 完全无法做到
- 7. 拒绝回答
- 8. 不确定
- 9. 不知道

SPSS WG Short Set Syntax Annotated with Output Tables Actual SPSS syntax is indented and the commands are in **BOLD text**. NOTE: For data analysis, use your standard weighting and estimation techniques.

The syntax below produces frequency distributions on each the six domains. Codes 7 (REFUSED), 8 (NOT ASCERTAINED) and 9 (DON'T KNOW) are INCLUDED as **MISSING**.

Step 1: Generate frequency distributions on each of the six domain variables.

FREQUENCIES VIS_SS HEAR_SS MOB_SS COM_SS SC_SS COG_SS.

VIS_SS

					Cumulative
		Frequency	Percent	Valid Percent	Percent
Valid	No difficulty	13690	79.0	81.6	81.6
	Some difficulty	2708	15.6	16.2	97.8
	A lot of difficulty	333	1.9	2.0	99.8
	Cannot do at all	36	.2	.2	100.0
	Total	16767	96.8	100.0	
Missing		559	3.2		
Total		17326	100.0		

HEAR_SS

					Cumulative
		Frequency	Percent	Valid Percent	Percent
Valid	No difficulty	13680	79.0	81.6	81.6
	Some difficulty	2753	15.9	16.4	98.0
	A lot of difficulty	310	1.8	1.8	99.9
	Cannot do at all	23	.1	.1	100.0
	Total	16766	96.8	100.0	
Missing		560	3.2		
Total		17326	100.0		

MOB_SS

					Cumulative
		Frequency	Percent	Valid Percent	Percent
Valid	No difficulty	13424	77.5	80.1	80.1
	Some difficulty	2165	12.5	12.9	93.0
	A lot of difficulty	792	4.6	4.7	97.7
	Cannot do at all	380	2.2	2.3	100.0
	Total	16761	96.7	100.0	
Missing		565	3.3		
Total		17326	100.0		

COM_SS

					Cumulative
		Frequency	Percent	Valid Percent	Percent
Valid	No difficulty	15874	91.6	94.7	94.7
	Some difficulty	745	4.3	4.4	99.2
	A lot of difficulty	94	.5	.6	99.7
	Cannot do at all	43	.2	.3	100.0
	Total	16756	96.7	100.0	
Missing		570	3.3		
Total		17326	100.0		

SC_SS

					Cumulative
		Frequency	Percent	Valid Percent	Percent
Valid	No difficulty	16029	92.5	95.7	95.7
	Some difficulty	544	3.1	3.2	98.9
	A lot of difficulty	114	.7	.7	99.6
	Cannot do at all	68	.4	.4	100.0
	Total	16755	96.7	100.0	
Missing		571	3.3		
Total		17326	100.0		

COG_SS

					Cumulative
		Frequency	Percent	Valid Percent	Percent
Valid	No difficulty	13719	79.2	81.9	81.9
	Some difficulty	2632	15.2	15.7	97.6
	A lot of difficulty	382	2.2	2.3	99.9
	Cannot do at all	20	.1	.1	100.0
	Total	16753	96.7	100.0	
Missing		573	3.3		
Total		17326	100.0		

Step 2: Calculate a variable, SUM_234

SUM_234 summates the number of domains coded SOME DIFFICULTY (2) or A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4) for each person. This new variable is used in the determination of disability identifiers: DISABILITY1 and DISABILITY2.

The syntax below **counts** the number of domains/questions a person has that are coded SOME DIFFICULTY (2) or A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4).

Possible range 0: no difficulties in any domain, to 6: all six domains coded SOME DIFFICULTY (2) or A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4).

MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

COUNT SUM_234 = VIS_SS HEAR_SS MOB_SS COM_SS COG_SS SC_SS (2 thru 4). IF (MISSING(VIS_SS) AND MISSING(HEAR_SS) AND MISSING(MOB_SS) AND MISSING(COM_SS) AND MISSING(COG_SS)) SUM_234 = 9. RECODE SUM_234 (9=SYSMIS).

FREQUENCIES SUM_234.

SUM 234

				Valid	Cumulative
		Frequency	Percent	Percent	Percent
Valid	.00	9266	53.5	55.2	55.2
	1.00	3839	22.2	22.9	78.1
	2.00	1892	10.9	11.3	89.4
	3.00	989	5.7	5.9	95.3
	4.00	481	2.8	2.9	98.2
	5.00	232	1.3	1.4	99.5
	6.00	78	.5	.5	100.0
	Total	16777	96.8	100.0	
Missing		549	3.2		
Total		17326	100.0		

Step 3: Calculate a variable, SUM_34

SUM_34 summates the number of domains_coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4) for each person. This new variable is used in the determination of disability identifier: DISABILITY2.

The syntax below counts the number of domains/questions a person has that are coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4)

Possible range 0: no difficulties coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4) in any domain, to 6: all six domains coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4). MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

COUNT SUM_34 = VIS_SS HEAR_SS MOB_SS COM_SS COG_SS SC_SS (3 thru 4).

IF (MISSING(VIS_SS) AND MISSING(HEAR_SS) AND MISSING(MOB_SS) AND MISSING(COM_SS) AND MISSING(SC_SS) AND MISSING(COG_SS)) SUM_34 = 9.

RECODE SUM_34 (9=SYSMIS).

FREQUENCIES SUM_34.

SU	\mathbf{M}	34
\mathbf{v}	TAT	J T

			~ ~		
				Valid	Cumulative
		Frequency	Percent	Percent	Percent
Valid	.00	14905	86.0	88.8	88.8
	1.00	1367	7.9	8.1	97.0
	2.00	345	2.0	2.1	99.0
	3.00	117	.7	.7	99.7
	4.00	31	.2	.2	99.9
	5.00	9	.1	.1	100.0
	6.00	3	.0	0.	100.0
	Total	16777	96.8	100.0	
Missing		549	3.2		
Total		17326	100.0		

Step 4: Calculate Disability Identifier: DISABILITY1

The syntax below calculates the first disability identifier: **DISABILITY1** where the level of inclusion is at least one domain/question is coded SOME DIFFICULTY or A LOT OF DIFFICULTY or CANNOT DO AT ALL.

MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

COMPUTE DISABILITY1 = 0.

IF (MISSING(VIS_SS) AND MISSING(HEAR_SS) AND MISSING(MOB_SS) AND MISSING(COM_SS) AND MISSING(SC_SS) AND MISSING(COG_SS)) DISABILITY1 = 9.

IF (SUM 234 >= 1) DISABILITY1 = 1.

NOTE: $SUM_{234} >= 1$ means that at least one of the six domains is coded at least SOME DIFFICULTY (2).

VALUE LABELS DISABILITY1 0 'without disability' 1 'with disability'. RECODE DISABILITY1 (9=SYSMIS). FREQUENCIES DISABILITY1.

DISABILITY1

				Valid	Cumulative	Weighted
		Frequency	Percent	Percent	Percent	Percent*
Valid	without disability	9266	53.5	55.2	55.2	58.1
	with disability	7511	43.4	44.8	100.0	41.9
	Total	16777	96.8	100.0		100.0
Missing		549	3.2			
Total		17326	100.0			

^{*}Weighted estimate provided – but is not part of the SPSS syntax.

Step 5: Calculate Disability Identifier: DISABILITY2

The syntax below calculates the second disability identifier: **DISABILITY2** where the level of inclusion is: at least 2 domains/questions are coded SOME DIFFICULTY or any 1 domain/question is coded A LOT OF DIFFICULTY or CANNOT DO AT ALL.

MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

COMPUTE DISABILITY2 = 0.

IF (MISSING(VIS_SS) AND MISSING(HEAR_SS) AND MISSING(MOB_SS) AND MISSING(COM_SS) AND MISSING(SC_SS) AND MISSING(COG_SS)) DISABILITY2 = 9.

IF $(SUM_234 >= 2 OR SUM_34 = 1) DISABILITY2 = 1.$

NOTE: The above syntax identifies those with at least two of the six domains coded as at least SOME DIFFICULTY (2): SUM_234 >= 2, OR those who have one domain that is coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4): SUM_34 = 1.

VALUE LABELS DISABILITY2 0 'without disability' 1 'with disability'. RECODE DISABILITY2 (9=SYSMIS). FREQUENCIES DISABILITY2.

DISABILITY2

				Valid	Cumulative	Weighted
		Frequency	Percent	Percent	Percent	Percent*
Valid	without disability	12707	73.3	75.7	75.7	78.3
	with disability	4070	23.5	24.3	100.0	21.7
	Total	16777	96.8	100.0		100.0
Missing		549	3.2			
Total		17326	100.0			

^{*}Weighted estimate provided – but is not part of the SPSS syntax.

Step 6: Calculate Disability Identifier: DISABILITY3

The syntax below calculates the third disability identifier: **DISABILITY3** where the level of inclusion is: any 1 domain/question is coded A LOT OF DIFFICULTY or CANNOT DO AT ALL. MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

THIS IS THE CUT-OFF RECOMMENDED BY THE WG.

COMPUTE DISABILITY3 = 0.

IF (MISSING(VIS_SS) AND MISSING(HEAR_SS) AND MISSING(MOB_SS) AND MISSING(COM SS) AND MISSING(SC SS) AND MISSING(COG SS)) DISABILITY3 = 9.

IF ((VIS_SS = 3 or VIS_SS = 4) or (HEAR_SS = 3 or HEAR_SS = 4) or (MOB_SS = 3 or MOB_SS = 4) or (COM_SS = 3 or COM_SS = 4) or (SC_SS = 3 or SC_SS = 4) or (COG_SS = 3 or COG_SS = 4)) DISABILITY3 = 1.

VALUE LABELS DISABILITY3 0 'without disability' 1 'with disability'. RECODE DISABILITY3 (9=SYSMIS). FREQUENCIES DISABILITY3.

DISABILITY3

				Valid	Cumulative	Weighted
		Frequency	Percent	Percent	Percent	Percent*
Valid	without disability	14905	86.0	88.8	88.8	90.5
	with disability	1872	10.8	11.2	100.0	9.5
	Total	16777	96.8	100.0		100.0
Missing		549	3.2			
Total		17326	100.0			

^{*}Weighted estimate provided – but is not part of the SPSS syntax.

Step 7: Calculate Disability Identifier: DISABILITY4

The syntax below calculates the fourth disability identifier: **DISABILITY4** where the level of inclusion is any one domain is coded CANNOT DO AT ALL (4).

MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

COMPUTE DISABILITY4 = 0.

IF (MISSING(VIS_SS) AND MISSING(HEAR_SS) AND MISSING(MOB_SS) AND MISSING(COM_SS) AND MISSING(SC_SS) AND MISSING(COG_SS)) DISABILITY4 = 9.

IF $((VIS_SS = 4) \text{ or } (HEAR_SS = 4) \text{ or } (MOB_SS = 4) \text{ or } (COM_SS = 4) \text{ or } (SC_SS = 4) \text{ or } (COG_SS = 4))$ DISABILITY4 = 1.

VALUE LABELS DISABILITY4 0 'without disability' 1 'with disability'. **RECODE** DISABILITY4 (9=SYSMIS).

FREQUENCIES DISABILITY4.

DISABILITY4

				Valid	Cumulative	Weighted
		Frequency	Percent	Percent	Percent	Percent*
Valid	without disability	16312	94.1	97.2	97.2	97.8
	with disability	465	2.7	2.8	100.0	2.2
	Total	16777	96.8	100.0		100.0
Missing		549	3.2			
Total		17326	100.0			

^{*}Weighted estimate provided – but is not part of the SPSS syntax.