

Washington Group on Disability Statistics

12 May 2020

Analytic Guidelines: Creating Disability Identifiers Using the Washington Group Short Set on Functioning (WG-SS) Stata Syntax

Introduction

Disability is best understood as a continuum. In terms of difficulty functioning, the 'difficulty' can be operationalized through a range of descriptors from no difficulty at all, through some difficulty and a lot of difficulty to completely unable to carry out the action. Each of these descriptors represents a cut-off or threshold in the determination of a final disability identifier; for example, to define those with and without disability. These levels of functioning are also represented in the response categories to the WG Short Set on Functioning (WG-SS).

Disability prevalence is not a single statistic, but can be calculated at various thresholds depending on the purposes of both data collection and reporting. For example, if the purpose is to provide for equitable access to public spaces – then the level of inclusion for a disability identifier might be *some difficulty*, since those with even minor levels of difficulty functioning would likely benefit from adaptations made to remove barriers and ease access. The installation of escalators in place of stairs, for instance, is a common universal design element that benefits persons with a wide range of mobility difficulty. Alternatively, if the purpose is to provide subsidies or allowances – the level of inclusion for a disability identifier might be *cannot do at all* since only those with more severe functional limitations would meet stricter eligibility criteria.

The Stata syntax described in this document provides for the calculation of four disability identifiers at four thresholds. The population of those *with disability* using these four different thresholds produces the following four disability identifiers:

The Washington Group Implementation Documents

cover the tools developed by the Washington Group on Disability Statistics (WG) to collect internationally comparable disability data on censuses and surveys. The documents address best practices in implementing the Short Set, Extended Set, Short Set - Enhanced, the WG / UNICEF Child Functioning Modules for children 2-4 and 5-17 years of age, and the WG / ILO LFS Disability Module, as well as other WG tools. Topics include translation, question specifications, analytic guidelines, programming code for analyses, the use of the tools for the purposes of disaggregation, and more.

To locate other WG Implementation Documents and more information, visit the Washington Group website: http://www.washingtongroup-disability.com/.

- DISABILITY1: the level of inclusion is at least one domain/question is coded SOME DIFFICULTY or A LOT OF DIFFICULTY or CANNOT DO AT ALL.
- DISABILITY2: the level of inclusion is at least 2 domains/questions are coded SOME DIFFICULTY or any 1 domain/question is coded A LOT OF DIFFICULTY or CANNOT DO AT ALL.

• **DISABILITY3**: the level of inclusion is any 1 domain/question is coded A LOT OF DIFFICULTY or CANNOT DO AT ALL.

NOTE: DISABILITY3 IS THE CUT-OFF RECOMMENDED BY THE WG.

• **DISABILITY4**: the level of inclusion is any one domain is coded CANNOT DO AT ALL (4).

NOTE: The Stata syntax is based on the *variable labels and value labels* indicated in the tables below. Ensure that you use the same *variable and value labels* OR revise the Stata syntax to reflect the *labels* used in your database.

The WG-SS is administered as part of the U.S. National Health Interview Survey (NHIS). The data used to prepare these guidelines come from the 2013 NHIS.

Note to users of the NHIS: the variable names in the NHIS data file and documentation may differ from those used in this document; e.g., the self-care domain variable referenced as SC-SS in this document is referred to as UB_SS in the NHIS data file and documentation.

| WG Short Set Questions/Domains | Variable Label |
|---|----------------|
| 1. Do you have difficulty seeing even if wearing glasses? | VIS_SS |
| 2. Do you have difficulty hearing even if using a hearing aid? | HEAR_SS |
| 3. Do you have difficulty walking or climbing stairs? | MOB_SS |
| 4. Do you have difficulty remembering or concentrating? | COG_SS |
| 5. Do you have difficulty with (self-care such as) washing all over or dressing | ?? SC_SS |
| 6. Using your usual language, do you have difficulty communicating (for example understanding or being understood by others)? | COM_SS |

The value labels used for each of the WG-SS questions are:

- 1. No difficulty
- 2. Yes, some difficulty
- 3. Yes, a lot of difficulty
- 4. Cannot do at all
- 7. Refused
- 8. Not ascertained
- 9. Don't know

Stata WG Short Set Syntax Annotated with Output Tables

Actual Stata syntax is indented and are in **Bold text**.

NOTE: For data analysis, use your standard weighting and estimation techniques.

The syntax below produces frequency distributions on each the six domains. Codes 7 (REFUSED), 8 (NOT ASCERTAINED) and 9 (DON'T KNOW) are RECODED as **MISSING**.

Step 1: Generate frequency distributions on each of the six domain variables.

VIS_SS is the WG-SS Vision question.

```
gen Vision=VIS_SS if inlist(VIS_SS, 1, 2, 3, 4) replace Vision=. if inlist(VIS_SS, 7, 8, 9) tabulate Vision
```

Vision: Degree of difficulty seeing

| | | | | | Cumulative |
|---------|---------------------|-----------|---------|---------------|------------|
| | | Frequency | Percent | Valid Percent | Percent |
| Valid | No difficulty | 13690 | 79.0 | 81.6 | 81.6 |
| | Some difficulty | 2708 | 15.6 | 16.2 | 97.8 |
| | A lot of difficulty | 333 | 1.9 | 2.0 | 99.8 |
| | Cannot do at all | 36 | .2 | .2 | 100.0 |
| | Total | 16767 | 96.8 | 100.0 | |
| Missing | | 559 | 3.2 | | |
| Total | | 17326 | 100.0 | | |

HEAR_SS is the WG-SS Hearing question.

```
gen Hearing=HEAR_SS if inlist(HEAR_SS, 1, 2, 3, 4) replace Hearing=. if inlist(HEAR_SS, 7, 8, 9) tabulate Hearing
```

Hearing: Degree of difficulty hearing

| | | | | | Cumulative |
|---------|---------------------|-----------|---------|---------------|------------|
| | | Frequency | Percent | Valid Percent | Percent |
| Valid | No difficulty | 13680 | 79.0 | 81.6 | 81.6 |
| | Some difficulty | 2753 | 15.9 | 16.4 | 98.0 |
| | A lot of difficulty | 310 | 1.8 | 1.8 | 99.9 |
| | Cannot do at all | 23 | .1 | .1 | 100.0 |
| | Total | 16766 | 96.8 | 100.0 | |
| Missing | | 560 | 3.2 | | |
| Total | | 17326 | 100.0 | | |

MOB_SS is the WG-SS Mobility question.

```
gen Mobility=MOB_SS if inlist(MOB_SS, 1, 2, 3, 4) replace Mobility=. if inlist(MOB_SS, 7, 8, 9) tabulate Mobility
```

Mobility: Degree of difficulty walking or climbing steps

| | | | | | Cumulative |
|---------|---------------------|-----------|---------|---------------|------------|
| | | Frequency | Percent | Valid Percent | Percent |
| Valid | No difficulty | 13424 | 77.5 | 80.1 | 80.1 |
| | Some difficulty | 2165 | 12.5 | 12.9 | 93.0 |
| | A lot of difficulty | 792 | 4.6 | 4.7 | 97.7 |
| | Cannot do at all | 380 | 2.2 | 2.3 | 100.0 |
| | Total | 16761 | 96.7 | 100.0 | |
| Missing | | 565 | 3.3 | | |
| Total | | 17326 | 100.0 | | |

COM_SS is the WG-SS Communication question.

```
gen Communication=COM_SS if inlist(COM_SS, 1, 2, 3, 4) replace Communication=. if inlist(COM_SS, 7, 8, 9) tabulate Communication
```

Communication: Degree of difficulty communicating using usual language

| | | | | | Cumulative |
|---------|---------------------|-----------|---------|---------------|------------|
| | | Frequency | Percent | Valid Percent | Percent |
| Valid | No difficulty | 15874 | 91.6 | 94.7 | 94.7 |
| | Some difficulty | 745 | 4.3 | 4.4 | 99.2 |
| | A lot of difficulty | 94 | .5 | .6 | 99.7 |
| | Cannot do at all | 43 | .2 | .3 | 100.0 |
| | Total | 16756 | 96.7 | 100.0 | |
| Missing | | 570 | 3.3 | | |
| Total | | 17326 | 100.0 | | |

SC_SS is the WG-SS Self-care question.

```
gen Self_Care=SC_SS if inlist(SC_SS, 1, 2, 3, 4) replace Self_Care=. if inlist(SC_SS, 7, 8, 9) tabulate Self_Care
```

Self_Care Degree of difficulty with self-care

| | | | | | Cumulative |
|---------|---------------------|-----------|---------|---------------|------------|
| | | Frequency | Percent | Valid Percent | Percent |
| Valid | No difficulty | 16029 | 92.5 | 95.7 | 95.7 |
| | Some difficulty | 544 | 3.1 | 3.2 | 98.9 |
| | A lot of difficulty | 114 | .7 | .7 | 99.6 |
| | Cannot do at all | 68 | .4 | .4 | 100.0 |
| | Total | 16755 | 96.7 | 100.0 | |
| Missing | | 571 | 3.3 | | |
| Total | | 17326 | 100.0 | | |

COG_SS is the WG-SS Cognition question.

gen Cognition=COG_SS **if inlist**(COG_SS, 1, 2, 3, 4) **replace** Cognition=. **if inlist**(COG_SS, 7, 8, 9) **tabulate** Cognition

Cognition: Degree of difficulty remembering or concentrating

| | | | | | Cumulative |
|---------|---------------------|-----------|---------|---------------|------------|
| | | Frequency | Percent | Valid Percent | Percent |
| Valid | No difficulty | 13719 | 79.2 | 81.9 | 81.9 |
| | Some difficulty | 2632 | 15.2 | 15.7 | 97.6 |
| | A lot of difficulty | 382 | 2.2 | 2.3 | 99.9 |
| | Cannot do at all | 20 | .1 | .1 | 100.0 |
| | Total | 16753 | 96.7 | 100.0 | |
| Missing | 5 | 573 | 3.3 | | |
| Total | | 17326 | 100.0 | | |

Step 2: Calculate a variable, SUM_234

SUM_234 summates the number of domains coded SOME DIFFICULTY (2) or A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4) for each person. This new variable is used in the determination of disability identifiers: DISABILITY1 and DISABILITY2.

The syntax below **counts** the number of domains/questions a person has that are coded SOME DIFFICULTY (2) or A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4).

Possible range 0: no difficulties in any domain, to 6: all six domains coded SOME DIFFICULTY (2) or A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4).

MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

```
gen SumPoints=0
foreach v of var Vision Hearing Mobility Cognition Self_Care Communication{
    replace SumPoints=SumPoints + inlist(`v',2,3,4)
}
replace SumPoints=. if missing(Vision) & missing(Hearing) & ///
missing(Mobility) & missing(Cognition) & missing(Self_Care) & missing(Communication)

gen SUM_234=. if SumPoints==.
replace SUM_234=1 if SumPoints==1
replace SUM_234=2 if SumPoints==2
replace SUM_234=3 if SumPoints==3
replace SUM_234=4 if SumPoints==4
replace SUM_234=5 if SumPoints==5
replace SUM_234=6 if SumPoints==6
replace SUM_234=0 if SumPoints==0
tabulate SUM_234
```

SUM 234

| | | | | Valid | Cumulative |
|---------|-------|-----------|---------|---------|------------|
| | | Frequency | Percent | Percent | Percent |
| Valid | .00 | 9266 | 53.5 | 55.2 | 55.2 |
| | 1.00 | 3839 | 22.2 | 22.9 | 78.1 |
| | 2.00 | 1892 | 10.9 | 11.3 | 89.4 |
| | 3.00 | 989 | 5.7 | 5.9 | 95.3 |
| | 4.00 | 481 | 2.8 | 2.9 | 98.2 |
| | 5.00 | 232 | 1.3 | 1.4 | 99.5 |
| | 6.00 | 78 | .5 | .5 | 100.0 |
| | Total | 16777 | 96.8 | 100.0 | |
| Missing | | 549 | 3.2 | | |
| Total | | 17326 | 100.0 | | |

Step 3: Calculate a variable, SUM_34

SUM_34 summates the number of domains_coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4) for each person. This new variable is used in the determination of disability identifier: DISABILITY2.

The syntax below counts the number of domains/questions a person has that are coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4)

Possible range 0: no difficulties coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4) in any domain, to 6: all six domains coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4). MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

```
gen SumPoints2=0
foreach v of var Vision Hearing Mobility Cognition Self_Care Communication{
    replace SumPoints2=SumPoints2 + inlist(`v',3,4)
}
replace SumPoints2=. if missing(Vision) & missing(Hearing) & ///
missing(Mobility) & missing(Cognition) & missing(Self_Care) & missing(Communication)

gen SUM_34=. if Sumpoints2==.
replace SUM_34=1 if SumPoints2==1
replace SUM_34=2 if SumPoints2==2
replace SUM_34=3 if SumPoints2==3
replace SUM_34=4 if SumPoints2==4
replace SUM_34=5 if SumPoints2==5
replace SUM_34=6 if SumPoints2==6
replace SUM_34=0 if SumPoints2==0
tabulate SUM_34
```

SUM 34

| | | _ | _ | Valid | Cumulative |
|---------|-------|-----------|---------|---------|------------|
| | | Frequency | Percent | Percent | Percent |
| Valid | .00 | 14905 | 86.0 | 88.8 | 88.8 |
| | 1.00 | 1367 | 7.9 | 8.1 | 97.0 |
| | 2.00 | 345 | 2.0 | 2.1 | 99.0 |
| | 3.00 | 117 | .7 | .7 | 99.7 |
| | 4.00 | 31 | .2 | .2 | 99.9 |
| | 5.00 | 9 | .1 | .1 | 100.0 |
| | 6.00 | 3 | .0 | 0. | 100.0 |
| | Total | 16777 | 96.8 | 100.0 | |
| Missing | | 549 | 3.2 | | |
| Total | | 17326 | 100.0 | | |

Step 4: Calculate Disability Identifier: **DISABILITY1**

The syntax below calculates the first disability identifier: **DISABILITY1** where the level of inclusion is at least one domain/question is coded SOME DIFFICULTY or A LOT OF DIFFICULTY or CANNOT DO AT ALL.

MISSING (.) are those who have coded 7, 8 or 9 on all six domains.

```
gen Disability1=2
replace Disability1=1 if SUM_234 >=1
replace Disability1=. if missing(Vision) & missing(Hearing) & missing(Mobility) & ///
missing(Cognition) & missing(Self_Care) & missing(Communication)
```

NOTE: SUM_234 >= 1 means that at least one of the six domains is coded at least SOME DIFFICULTY (2).

tabulate Disability1

DISABILITY1

| | | | | Valid | Cumulative | Weighted |
|---------|--------------------|-----------|---------|---------|------------|----------|
| | | Frequency | Percent | Percent | Percent | Percent* |
| Valid | without disability | 9266 | 53.5 | 55.2 | 55.2 | 58.1 |
| | with disability | 7511 | 43.4 | 44.8 | 100.0 | 41.9 |
| | Total | 16777 | 96.8 | 100.0 | | 100.0 |
| Missing | | 549 | 3.2 | | | |
| Total | | 17326 | 100.0 | | | |

^{*}Weighted estimate provided – but is not part of the Stata syntax.

Step 5: Calculate Disability Identifier: DISABILITY2

The syntax below calculates the second disability identifier: **DISABILITY2** where the level of inclusion is: at least 2 domains/questions are coded SOME DIFFICULTY or any 1 domain/question is coded A LOT OF DIFFICULTY or CANNOT DO AT ALL.

MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

```
gen Disability2=2
replace Disability2=1 if (SUM_234 >=2 | SUM_34==1)
replace Disability2=. if missing(Vision) & missing(Hearing) & missing(Mobility) & ///
missing(Cognition) & missing(Self Care) & missing(Communication)
```

NOTE: The above syntax identifies those with at least two of the six domains coded as at least SOME DIFFICULTY (2): $SUM_234 >= 2$, OR those who have one domain that is coded A LOT OF DIFFICULTY (3) or CANNOT DO AT ALL (4): $SUM_34 = 1$.

tabulate Disability2

DISABILITY2

| | | | | Valid | Cumulative | Weighted |
|---------|--------------------|-----------|---------|---------|------------|----------|
| | | Frequency | Percent | Percent | Percent | Percent* |
| Valid | without disability | 12707 | 73.3 | 75.7 | 75.7 | 78.3 |
| | with disability | 4070 | 23.5 | 24.3 | 100.0 | 21.7 |
| | Total | 16777 | 96.8 | 100.0 | | 100.0 |
| Missing | | 549 | 3.2 | | | |
| Total | | 17326 | 100.0 | | | |

^{*}Weighted estimate provided – but is not part of the Stata syntax.

Step 6: Calculate Disability Identifier: DISABILITY3

The syntax below calculates the third disability identifier: **DISABILITY3** where the level of inclusion is: any 1 domain/question is coded A LOT OF DIFFICULTY or CANNOT DO AT ALL. MISSING (9) are those who have coded 7, 8 or 9 on all six domains.

THIS IS THE CUT-OFF RECOMMENDED BY THE WG.

```
gen Disability3=2
replace Disability3=1 if (inlist(Vision,3,4) | inlist(Hearing,3,4) | inlist(Mobility,3,4) | ///
inlist(Communication,3,4) | inlist(Self_Care,3,4) | inlist(Cognition,3,4))
replace Disability3=. if missing(Vision) & missing(Hearing) & missing(Mobility) & ///
missing(Cognition) & missing(Self_Care) & missing(Communication)
```

tabulate Disability3

DISABILITY3

| | | | | Valid | Cumulative | Weighted |
|---------|--------------------|-----------|---------|---------|------------|----------|
| | | Frequency | Percent | Percent | Percent | Percent* |
| Valid | without disability | 14905 | 86.0 | 88.8 | 88.8 | 90.5 |
| | with disability | 1872 | 10.8 | 11.2 | 100.0 | 9.5 |
| | Total | 16777 | 96.8 | 100.0 | | 100.0 |
| Missing | | 549 | 3.2 | | | |
| Total | | 17326 | 100.0 | | | |

^{*}Weighted estimate provided – but is not part of the Stata syntax.

Step 7: Calculate Disability Identifier: **DISABILITY4**

The syntax below calculates the fourth disability identifier: **DISABILITY4** where the level of inclusion is any one domain is coded CANNOT DO AT ALL (4).

MISSING (.) are those who have coded 7, 8 or 9 on all six domains.

```
gen Disability4=2
replace Disability4=1 if ((Vision==4) | (Hearing==4) | (Mobility==4) | (Communication==4) | ///
(Self_Care==4) | (Cognition==4))
replace Disability4=. if missing(Vision) & missing(Hearing) & missing(Mobility) & ///
missing(Cognition) & missing(Self_Care) & missing(Communication)
tabulate Disability4
```

DISABILITY4

| | | | | Valid | Cumulative | Weighted |
|---------|--------------------|-----------|---------|---------|------------|----------|
| | | Frequency | Percent | Percent | Percent | Percent* |
| Valid | without disability | 16312 | 94.1 | 97.2 | 97.2 | 97.8 |
| | with disability | 465 | 2.7 | 2.8 | 100.0 | 2.2 |
| | Total | 16777 | 96.8 | 100.0 | | 100.0 |
| Missing | | 549 | 3.2 | | | |
| Total | | 17326 | 100.0 | | | |

^{*}Weighted estimate provided – but is not part of the Stata syntax.